VEHICLE SPECIFICATIONS

Price Source and Listings

VEHICLE SPECIFICATIONS

SPECIFICATION	VOLKSWAGEN PANEL	CHEVROLET	FORD DELIVERY VAN
Gross Vehicle Weight	4,112 lbs.	4,600 lbs.	3,300 lbs.
Payload—Standard	1.830 lbs.	1,900 lbs.	900 lbs.
Wheelbase	94.5 in.	95 in.	90 in.
Overall Length	168.9 in.	179.7 in.	168.4 in.
Overall Width	68.9 in.	70 in.	78.2 in.
Overall Height	76.4 in.	68.5 in.	75.8 in.
Ground Clearance	9.5 in.	6.5 in.	6.2 in.
Turning Circle Diameter	39 ft.	39 ft.	31.5 ft.
Floor Loading Line-Side	19.7 in.	13.7 in.	25 in.
Floor Loading Line—Rear	38.6 in.	26.5 in.	26 in.
Side Door Height	47.2 in.	49 in.	47.8 in.
Side Door Width	46 in.	53.5 in.	49.4 in.
Rear Door Height	28.7 in.	36 in.	47.8 in.
Rear Door Width	35.4 in.	44.7 in.	49.4 in.
Loading Space Length	106.3 in.	106.3 in.	106 in.
Loading Space Width	59.1 in.	60.2 in.	65 in.
Loading Space Height	53.1 in.	54 in.	54.3 in.
Driver Cabin Headroom	38 in.	35 in.	36 in.
Engine Horsepower— Max. @ R.P.M.	40 @ 3,900	80 @ 4,400	85 @ 4,200
Engine Cylinders-Number	4	6	6
Engine Bore & Stroke	3.03 x 2.52 in.	3.43 x 2.60 in.	3.50 x 2.50 in.
Engine Piston Displacement	72.74 cu. in.	145 cu. in.	144.3 cu. in.
Engine Compression Ratio Engine Torque—Max. Ft. Lb.	7-to-1	8-to-1	8.7-to-1
@ R.P.M.	64 @ 2,400	128 @ 2,300	134 @ 2,000
Engine Cooling System	AIR	AIR	WATER
Engine Location in Vehicle	REAR	REAR	FRONT
Fuel Tank Capacity	10.6 gals.	18.5 gals.	14 gals.
Transmission Speeds—Forward	4	3	3
Transmission Type	Full Synchromesh	Synchromesh	Synchrosilent
Front Suspension	Independent Torsion Bar	Independent Coil	Rigid-Semi- Ellipt Leaf
Rear Suspension	Independent Torsion Bar	Independent Coil	Rigid-Semi- Ellipt Leaf
Tire Size	6:40 x 15	7:00 x 14	6:50 x 13

VEHICLE SPECIFICATIONS

SPECIFICATION	VOLKSWAGEN PANEL	CHEVROLET	FORD DELIVERY VAN
Gross Vehicle Weight	4,112 lbs.	4,600 lbs.	3,300 lbs.
Payload—Standard	1.830 lbs.	1,900 lbs.	900 lbs.
Wheelbase	94.5 in.	95 in.	90 in.
Overall Length	168.9 in.	179.7 in.	168.4 in.
Overall Width	68.9 in.	70 in.	78.2 in.
Overall Height	76.4 in.	68.5 in.	75.8 in.
Ground Clearance	9.5 in.	6.5 in.	6.2 in.
Turning Circle Diameter	39 ft.	39 ft.	31.5 ft.
Floor Loading Line-Side	19.7 in.	13.7 in.	25 in.
Floor Loading Line—Rear	38.6 in.	26.5 in.	26 in.
Side Door Height	47.2 in.	49 in.	47.8 in.
Side Door Width	46 in.	53.5 in.	49.4 in.
Rear Door Height	28.7 in.	36 in.	47.8 in.
Rear Door Width	35.4 in.	44.7 in.	49.4 in.
Loading Space Length	106.3 in.	106.3 in.	106 in.
Loading Space Width	59.1 in.	60.2 in.	65 in.
Loading Space Height	53.1 in.	54 in.	54.3 in.
Driver Cabin Headroom	38 in.	35 in.	36 in.
Engine Horsepower— Max. @ R.P.M.	40 @ 3,900	80 @ 4,400	85 @ 4,200
Engine Cylinders-Number	4	6	6
Engine Bore & Stroke	3.03 x 2.52 in.	3.43 x 2.60 in.	3.50 x 2.50 in.
Engine Piston Displacement	72.74 cu. in.	145 cu. in.	144.3 cu. in.
Engine Compression Ratio Engine Torque—Max. Ft. Lb.	7-to-1	8-to-1	8.7-to-1
@ R.P.M.	64 @ 2,400	128 @ 2,300	134 @ 2,000
Engine Cooling System	AIR	AIR	WATER
Engine Location in Vehicle	REAR	REAR	FRONT
Fuel Tank Capacity	10.6 gals.	18.5 gals.	14 gals.
Transmission Speeds—Forward	4	3	3
Transmission Type	Full Synchromesh	Synchromesh	Synchrosilent
Front Suspension	Independent Torsion Bar	Independent Coil	Rigid-Semi- Ellipt Leaf
Rear Suspension	Independent Torsion Bar	Independent Coil	Rigid-Semi- Ellipt Leaf
Tire Size	6:40 x 15	7:00 x 14	6:50 x 13



. . . for use by VW Dealership Personnel