NECC Technical Inspection Form



Owner's Name

| enicle Color | venicie Number(s) | NECC Class | |
|--------------------------------|---|-------------------------|-----------|
| wner/Driver(s) must present ca | ar with all items completed. Inspectors w | rill check compliance. | |
| | | Owner | Inspector |
| Exterior: | Number Visible- Front, Sides | | |
| | All glass and netting intact 1d | | |
| Wheels: | Hub caps/trim rings off | | |
| | Lug nuts—correct type | | |
| | Lug nuts—tight | | |
| Tires: | Tread depth of 1/16" min. on DOT tires | | |
| | No cuts, bulges, visible cord, etc. | | |
| | Valve stems serviceable | | |
| Trunk & Gas Cap: | Loose items, jack & spare out | | |
| | Master cylinder full | | |
| | Gas cap secure | | |
| Mirrors: | 1 inside or 2 outside | | |
| Front Suspension: | Wheel bearings | | |
| | Ball joints (Jack-Up-Test) | | |
| | Steering components | | |
| | Brake hoses | | |
| | Sufficient shock damping | | |
| | Chassis clearance | | |
| Rear Suspension: | Bearings, joints, bushings | | |
| | Sufficient shock damping | | |
| Interior: | Loose & removable items out | | |
| | Extinguisher, if present, secure 1c | | |
| | Roll bar/cage, if req'd, to spec 1b & 2 | | |
| | Seat belt to spec ^{1a} | | |
| | Firewall intact | | |
| Brakes: | Hard-Harder test | | |
| | Functional Brake Light(s) | | |
| Engine Compartment: | Throttle action & return | | |
| | Spare, jack, loose items out | | |
| | Fluid leaks, harmonic balancer | | |
| Battery: | Secure | | |
| Helmet: | Snell SA or M not more than 10 yrs old | | |
| Clothing | Long pants/sleeves, fire resistant ³ | | |
| · · · · g | | | |
| Owner/Driver Signature | | NECC Inspector's Initia | als |
| _ | | • | |

Owners and Drivers are responsible for preparing and maintaining participating vehicles in safe condition. NECC and its representatives and affiliates are not responsible for the failure of any components or for any incidents related or consequential to such failure. For more information, see NECC Rulebook for Cars and Drivers at <u>neccmotorsports.com</u>.

- 1. Competition-Prepared Vehicles must be equipped with (a) 3-point body restraint belts with 2" webbing or better, (b) braced roll bar or cage, (c) fire extinguisher or other fire suppression system, and (d) driver window netting where practicable. A Competition-Prepared Vehicle is one that either (a) was manufactured specifically for racing, such as a formula racing car, or (b) is not street-legal because it lacks equipment or features the law requires to allow one to operate it legally on public roads at any time and without restriction.
- 2. Convertibles must be equipped with roll bar or cage. Factory roll bars generally acceptable.
- 3. See NECC Rulebook for Cars and Drivers for full explanation of clothing requirements.